

Product profile



PF4i

Mid-Range Printer

- **Strong, all-metal construction** and superior throughput for harsh industrial environments
- **Compact size** fits space constrained applications
- **Smart Printing capabilities** support stand-alone printer applications, eliminating PC expense and complexity
- **All-in-one, user-selectable printer languages** – Fingerprint/ Direct Protocol (DP), IPL, ZSim and DSIm – in every printer
- **Secure wireless connectivity:** CCX and WiFi® certified with WPA2
- **Integrated Ethernet**, USB host and device, and serial interface standard
- **Internet Protocol v6 (IPv6)** support
- **Interchangeable print head** provides choice of 203 or 300 dpi print resolution

A member of the smartest bar code printer family on the market, the Intermec PF4i is flexible and programmable, enabling customers to optimize their printing operations, streamline deployment, and achieve quick return on investment. Built to meet the needs of mission-critical applications, the rugged PF4i delivers advanced, secure connectivity and the latest network protocols, ensuring peace-of-mind today and a reliable, scalable solution for the long haul. The compact PF4i Mid-Range Printer is part of Intermec's complete line of smart, strong and secure industrial printers.

Smart

The PF4i's smart design features support increased productivity in demanding environments. As a Smart Printer, the PF4i can host stand-alone applications, developed through Intermec Fingerprint programming language, that reduce errors and streamline operational processes. Smart Printers can eliminate the PC and control other devices directly (such as scanners, scales, applicators), improving efficiency and decreasing infrastructure costs and complexity.

The PF4i's integrated device management and diagnostic capabilities, provided through Intermec SmartSystems™ and Wavelink Avalanche™, reduce downtime and simplify deployment.

With its user-selectable, all-in-one programming languages (Fingerprint, IPL, ZSim, DSIm), the PF4i fits existing IT infrastructures, deploying with drop-in simplicity to Intermec or mixed printer environments. Its secure, industry-standard connectivity options support easy integration and fast deployment.

Strong

The rugged, all-metal PF4i incorporates features that reduce downtime and minimize maintenance costs. Its enhanced self-strip option delivers consistent performance across multiple media types. Replacing printheads is fast and easy, thanks to the magnetic QuickMount™ printhead design. The PF4i is co-engineered and tested with Intermec labels and other media products, ensuring optimized, superior performance when used with genuine Intermec media.

Secure

Multiple interface options are available, including the highest level of secure wireless connectivity (WPA2). The industry's only printers available with WiFi- and CCX-Certification, Intermec industrial printers help maintain wireless network integrity and reduce configuration time. Every printer ships with Ethernet connectivity, as well as with emerging network protocol IPv6, ensuring long-term, enterprise scalability. Other

connectivity options – standard RS232 and USB ports, and optional parallel, double serial or industrial interfaces – provide additional integration flexibility.

The standard CompactFlash™ memory slot is complemented by new USB host and device support. Handy, inexpensive and PC-compatible, CompactFlash and USB memory technologies provide extra storage for Fingerprint programs, layouts, graphics*, fonts and firmware upgrades.

* Fingerprint only

Description

Direct thermal and thermal transfer label, ticket and tag printer. Also available in dark metallic enclosure.

Physical Characteristics

Length: 405 mm (15.9 in)

Height: 178 mm (7 in)

Width: 244 mm (9.6 in)

Weight: 8 kg (17.7 lbs.)

Print Specifications

Max. Width: 104 mm (4.09 in) at 203 dpi;

105.7 mm (4.16 in) at 300 dpi.

Max. Length: 4095 mm (161.2 in) at 203 dpi;

2730 mm (107.5 in) at 300 dpi.

Print Speed

100 – 200 mm/s (4 – 8 ips) variable (203 dpi)

100 – 150 mm/s (4 – 6 ips) variable (300 dpi)

Print Resolution

8 dots/mm (203 dpi)

11.8 dots/mm (300 dpi)

Media

Type: Labels & Tags

Max/Min Width: 114.3/ 25.4 mm (4.5/ 1 in)

Thickness: 3.0 to 7.5 mil

Configuration: Roll-fed or fanfold

Sensing: Gap, notch, black mark, continuous

Label Roll Max Diameter (long door): 152.4 mm (6 in)

Label Roll Max Diameter (short door): 213 mm (8.38 in)

Label Roll Core: 38-76mm (1.5-3 in)

Type: Ribbons

Ribbon Max Diameter: 62mm (2.4in)

Ribbon Length: 220m (approx. 9,000 in)

Core ID: 25.4 mm (1 in)

Type: Wax, mid-range, resin

Genuine Intermec Media: www.intermec.com/media

Interfaces

Standard:

- Ethernet 10/100 Mbps
- RS-232, up to 115.2 kB/s

Supported Serial Protocols:

- Fingerprint/Direct Protocol: XON/XOFF, ENQ/ACK, DTR, RTS/CTS
- IPL: XON/XOFF, Intermec Std. Protocol
- USB 2.0

Optional:

- Parallel IEEE 1284
- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop

Wireless:

- IEEE 802.11 b/g
- Wi-Fi Certified, CCX (Cisco®) version 3 Certified
- WEP, WPA, WPA2, 802.11x (EAP-TTLS, LEAP, PEAP, FAST), 802.11i
- Multiple industrial antenna options for maximized coverage

Supported Protocols:

TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.)
LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMPv3,
SMTP, SNMP-MIB II supported (over UDP/IP),
private enterprise MIB included.
Supports IPv4 and IPv6

Software

Printer Command Languages:

- IPL
- Fingerprint/Direct Protocol
- ZSim (ZPL)
- DSim (DPL)
- XML enabled for SAP® All and Oracle® WMS

Applications / Drivers:

- InterDriver™ Windows printer driver
- Intermec label design and print package
- PrintSet for printer configuration

Development Software:

- Intermec Fingerprint Application Builder™ (IFAB)

Device Management Support:

- SmartSystems™
- Wavelink Avalanche™

Bar Code Symbologies

All major 1D and 2D symbologies are supported.

Standards Supported

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); OGMARS; POSTNET; HIBCC; ISBT 128; GM1724; UPS shipping label; Global Transport label

Fonts

Scalable fonts including CP1252

Font cache for maximum performance

Non-Latin fonts and legacy fonts available.

Graphics

Supports PCX file format. (Fingerprint Only)

Other formats supported with Label Generation Tools

Memory

Standard: 16MB Flash memory, 32MB

SDRAM, 1 CompactFlash slot

Available: 1GB CompactFlash memory, multi-GB USB memory device (FAT16/FAT32 USB drivers supported)

Keypad Control Panel

Interactive numeric keypad control panel

Power Supply

AC Voltage: 90 to 265 VAC, 45 to 65Hz

PFC Regulation: IEC 61000-3-2

Power Consumption: Standby 15W; Peak 300W

Operating Environment

Ambient Operating Temperature:

+5°C to +40°C (+41°F to +104°F)

Storage Temperature: -20°C to +70°C (-4°F to +152°F)

Humidity: 20 to 80% non-condensing

Regulatory Approvals

CE (EN55022 Class A), FCC Class A, UL/cUL, C-Tick

Options

Integral self-strip unit with liner takeup, Label Taken Sensor (LTS), CompactFlash™ (CF) memory, various international double byte fonts, alphanumeric keyboard*, parallel interface board, additional serial interface board*, industrial interface board*, applicator interface board*, real time clock, media supply hub, cutter, label low sensor

*Not applicable when using IPL firmware



Company Name
123 Your Street
City, State Zip
123.456.7890
info@YourURL.com
www.YourURL.com

Intermec
PartnerNet

Intermec
SmartSystems™



Copyright © 2010 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611556-02F 10/10

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.