

Captuvo SL62 Series

Enterprise Sled for Apple iPad mini™

Honeywell's Captuvo SL62 enterprise sled encases the popular Apple® iPad mini™, transforming it into an enterprise-ready device for businesses that prefer the simplicity and familiarity of iOS, but need additional endurance and functionality built in for instant access to inventory, scanning and secure payment processing.

From the leader in barcode scanning technology, the Captuvo SL62 features an integrated scanner with Adaptus™ Imaging Technology 6.0. This enables fast and accurate reading of linear and 2D barcodes on product, government issued IDs, coupons or loyalty club cards.

The Captuvo SL62 sled provides a protective housing for all versions of the iPad mini increasing its ruggedness against wear and tear and is compatible with various applications such as price and product look-up, inventory management, and scanning items for purchase at point-of-sale. Battery power to the iPad mini is additionally supported by the SL62 to reduce downtime and maximize productivity.

An optional integrated magnetic stripe reader is also available, supporting encrypted and unencrypted data output, which facilitates secure, quick and easy processing of credit card transactions and allows associates to check-out customers on the spot, wherever they may be.

Compact and easy to hold with one hand, the Captuvo SL62 provides an opportunity for businesses to upsell products and services by engaging at the point of customer service. A mobile printer can also be worn at the hip at the same time to allow for instant receipt printing.

The Captuvo SL62 is the superior solution when it comes to constantly adhering to increasing customer demand for fast and high-quality service. This device will help users elevate their brand, empower employees, enhance customer experience, drive top-line growth and maintain customer loyalty.



Preliminary

Features

- **Second-to-None Scanning:** Increases productivity and throughput with an integrated and easy-to-use imager that provides aggressive scanning of linear and 2D bar codes. scope.
- **Protective Housing:** Keeps the iPad mini protected from abuse such as drops or bumps common to enterprise environments without blocking the larger screen.
- **Optional Encryption-Ready Magnetic Stripe Reader:** With third-party key injection, cardholder data is encrypted as the card is swiped, protecting sensitive data and retailers' reputations, while reducing PCI

Captuvo SL62 Technical Specifications

Mechanical

Dimensions (LxWxH) 224.5 mm × 152.7 mm × 34.25 mm (8.8" × 6.0" × 1.34")

Weight (without iPad mini/iPad mini with Retina display) *Imager Only Version: 720g (25.3 oz.)*

System Architecture

Device Compatibility *Apple® iPad mini
Apple® iPad mini with Retina display*

Input Voltage 5V

Interfaces *UART between SL62 Apple® iOS device; USB/UART between SL62 & PC*

I/O Ports *Custom Mini USB*

Power Supply 5V, 1A

Buttons *Two scan buttons at the back; power button (extension of iPad mini/iPad mini with Retina display button); volume button (extension of iPad mini/iPad mini with Retina display button) access to iPad mini/iPad mini with Retina display Home button*

Audio *Access to iPad mini/iPad mini with Retina display 3.5-mm stereo headphone minijack, speaker and microphone*

Camera *Access to iPad-mini/iPad mini with Retina display front and back cameras*

Scanner *Adaptus 6.0 Imaging Technology
N5600SR-BRO-1: N5600 Standard range (SR) imager with green LED aimer
N5600HD-BRO-1: N5600 High Density (HD) imager with green LED aimer
N5600ER-BRO-1: N5600 Extended range (SR) imager with green LED aimer*

Decode Capabilities *Reads standard 1D, PDF, 2D, Postal and OCR symbologies*

Magnetic Stripe Reader *Integrated 3-track bidirectional MSR reader (supports encrypted and unencrypted data output)*

Swipe Speed *3 to 75 inches per second*

Encryption Supported *DES, TDES, AES*

Key Management Supported *DUKPT*

Battery *Removable 1150mAh Lithium Ion battery*

Expected Hours of Operation *8 hours (SL62 + Apple® iPad mini®/iPad mini with Retina display)*

Expected Charge Time *iPad mini: 9 hours with wall adaptor, 5 hours with charge base
iPad mini with Retina display: 14 hours with wall adaptor, 8 hours with charge base*

Development Environment *Captuvo SDK for Apple® iOS 6 and iOS 7*

Application Software *Available on the Apple® App Store or via 3rd party application developers
(visit www.isvstore.com/iosapps for more information)*

Warranty *1 year factory warranty*

Accessories *Standard USB A to Custom Mini USB cable (included)*

Environmental

Operating Temperature *0°C to 35°C (32°F to 95°F)*

Storage Temperature *-20°C to 45°C (4°F to 113°F)*

Humidity *5% to 85% relative humidity, non-condensing*

Drop *Designed to withstand multiple 1.2 m (4') drops to concrete, all axis under room temperature*

Environmental Sealing *IP30*

ESD *±8 KV Direct & ±10 KV Air*

Apple and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries.

*For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance
For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies*



Company Name
123 Your Street
City, ST 12345
123.456.7890
Info@YourURL.com
www.YourURL.com

Honeywell